

Annual Maintenance Cost Factors

"The Devil Really is in the Details"

2004 Facilities and Asset Management Conference "Stewardship of Federal Assets – United Commitment to Excellence" Orlando Florida May 4-6, 2004



Casey Matthews, P.E.
Utah State Engineer
Bureau of Land Management



Presentation Outline


- Overview BLM "Stewardship Strategy"
- Background Annual Maintenance Requirement
- Objective Standardize the Annual Maintenance Process
- Approach Annual Maintenance Cost Factors
- Performance Metrics Internal and External Gauges of Success
- Challenges and Lessons Learned Ideas and Answers
- Summary





Overview - BLM "Stewardship Strategy"

- Strategic approach to asset stewardship
- Integrates all aspects of asset management
- Developed to provide a
 Reasonable, Consistent, and
 Auditable approach to
 Facility Management







Background – Annual Maintenance

- Annual Maintenance within the BLM includes:
 - → Preventive Maintenance
 - → Reactive Maintenance
 - Emergency Maintenance
 - Component Renewal
- Annual Maintenance planning is designed to provide for consistent Life Cycle Management of the Bureau's assets which include:
 - → 82,000 miles of Roadways
 - → 2,100 Recreation Sites
 - → 700 Administrative Sites
 - ♦ 800 Dams
 - → 900 Bridges











Objective – Standardize The Annual Maintenance Budget Process

- Develop Annual Maintenance standards that identify the "appropriate" level of expenditure for each facility asset in order to allow the BLM to maximize the public's investment.
- Utilize Annual Maintenance Standards as a mechanism to strategically manage the condition and performance of each facility asset through the lifecycle
 - Identifies appropriate levels of funding
 - Defines potential deferred maintenance or the consequences of less than full funding
 - Provides guidance to the field on investment levels, priorities and Bureau standards for facility Stewardship



Approach - Existing Annual Maintenance Budget Strategies

- No basis (Budgets without Basis)
- Previous budget adjusted
- Percent of revenue
- Percent of Current Replacement Value
- Percent of CRV age adjusted
- Standard cost factors
- Projections based on "Actuals"/Forecasting





Approach – Accurate Inventory and Asset Classification

- Identify unique Asset Types that impact annual maintenance decisions
- Develop definitions and standards for each asset type
- Standardize units of measure for each asset type
- Assign a unique asset type to each asset
- Based on approach similar to methodology currently in use within Department of Defense and NASA





Approach - Example 1 Administrative Building

- **DEFINITION:** A building primarily used for office/clerical space. Ancillary functions may be included such as miscellaneous storage and vehicle parking, so long as those functions support the primary use and represent less than 50% of the building area.
- **INCLUDES:** Building and associated systems within the building walls
- **EXCLUDES:** Any items or features outside the building walls even though the items or features may be attached to and/or support the building or its functions.











Approach - Example 2 Lift Station

• **DEFINITION:** Either pre-fabricated or individually constructed tank or vault with associated pump(s) and piping for the purpose of pressurizing a sanitary or storm sewer system, or elevating sanitary or storm sewer effluent so that subsequent portion of line is gravity flow.

INCLUDES:

- ▶ Tank or vault
- Pump(s)
- Manholes
- → Alarm

• EXCLUDES:

- Distribution systems
- → Treatment facilities
- Lagoons
- Storage facilities





Approach - Example 3 Aircraft Ramp

- DEFINITION: An area used for parking aircraft, or moving aircraft from a storage / maintenance area to a runway or helipad.
- INCLUDES:
 - Windsocks
 - Pavement markings
 - → Tie-downs/restraints
 - Ground clips
- EXCLUDES:

S. DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

- → Parking Areas
- Area Lighting
- Access Roads (see Site Roadways)
- → Signs
- Hangars
- Maintenance Shops







Approach - Asset Classification Codes

Asset Classification	UOM	Annual Sustainment Requirement	Current Replacement Value	Source
Visitor Information Center	SF	\$3.92	\$148.00	4
Vault Toilet – Simple	QTY	\$153.84	\$8,385	6
Vault Toilet - Complex	QTY	\$174.84	\$11,425	6
Steel Bridge - Vehicular	SY	\$17.09	\$678.18	3
Roadway – Surfaced	SY	\$0.99	\$37.60	1
Fixed Wing Runway - Surfaced	SY	\$1.18	\$91.76	3



Approach - Location Adjustment Factors

Location	State	Factor	
Cody Field Office	Wyoming	71.2%	
Eugene Field Office	Oregon	104.6%	
Alaska Fire Service	Alaska	106.9%	
Campbell Tract	Alaska	105.0%	
Lake Havasu	Arizona	92.3%	
Billings	Montana	82.6%	
Grand Junction	Colorado	84.1%	
Boise	Idaho	83.8%	





Approach – Direct Maintenance Cost

BUREAU OF LAND MANAGEMENT - ANNUAL MAINTENANCE BUDGET NEED SUMMARY

State: Colorado Fiscal Year: 2004
Field Office: Field Office 1 Report Date: 11/3/2003

Site: ALL Location Adjustment Multiplier: 1.08

Asset Type	Count	Quantity	Unit of Measure	Unit Cost Factor	Direct Maintenance Cost (Unadjusted)	Direct Maintenance Cost (Adjusted)
Building - Vault Toilet	14	252	SF	\$15.61	\$3,933.72	\$4,248.42
Building - Visitors Center	2	11,200	SF	\$3.82	\$42,784.00	\$46,206.72
Aircraft Ramp - Concrete	1	950	SY	\$91.76	\$87,172.00	\$94,145.76
Boat Ramp-Aggregate/Grave	4	9,700	SF	\$4.18	\$40,546.00	\$43,789.68
Corral-Steel Pipe or Panel	1	32,000	SF	\$1.11	\$35,520.00	\$38,361.60
Emergency Power Generation-Diesel	3	3	EA	\$20,000.00	\$60,000.00	\$64,800.00
Parking Lot - Concrete	2	1,200	SY	\$52.95	\$63,540.00	\$68,623.20
Parking Lot - Aggregate	1	400	SY	\$37.60	\$15,040.00	\$16,243.20
Roadway - Natural Surface ML3	10	18,400	SY	\$18.80	\$345,920.00	\$373,593.60
Roadway - Asphalt Surface ML4	5	5,260	SY	\$37.60	\$197,776.00	\$213,598.08
Sub-Total Annual Maintenance Need (Unadjusted):				\$892,231.72	\$963,610.26	





Approach – Bureau Full Cost

BUREAU OF LAND MANAGEMENT - ANNUAL MAINTENANCE BUDGET NEED SUMMARY

State: Colorado Fiscal Year: 2004
Field Office: Field Office 1 Report Date: 11/3/2003

Site: ALL Location Adjustment Multiplier: 1.08

Asset Type	Count	Quantity	Unit of Measure	Unit Cost Factor	Direct Maintenance Cost (Unadjusted)	Direct Maintenance Cost (Adjusted)
Building - Vault Toilet	14	252	SF	\$15.61	\$3,933.72	\$4,248.42
Building - Visitors Center	2	11,200	SF	\$3.82	\$42,784.00	\$46,206.72
Aircraft Ramp - Concrete	1	950	SY	\$91.76	\$87,172.00	\$94,145.76
Boat Ramp-Aggregate/Grave	4	9,700	SF	\$4.18	\$40,546.00	\$43,789.68
Corral-Steel Pipe or Panel	1	32,000	SF	\$1.11	\$35,520.00	\$38,361.60
Emergency Power Generation-Diesel	3	3	EA	\$20,000.00	\$60,000.00	\$64,800.00
Parking Lot - Concrete	2	1,200	SY	\$52.95	\$63,540.00	\$68,623.20
Parking Lot - Aggregate	1	400	SY	\$37.60	\$15,040.00	\$16,243.20
Roadway - Natural Surface ML3	10	18,400	SY	\$18.80	\$345,920.00	\$373,593.60
Roadway - Asphalt Surface ML4	5	5,260	SY	\$37.60	\$197,776.00	\$213,598.08
Sub-Total Annual Maintenance Need (Unadjusted):					\$892,231.72	\$963,610.26

FULL BUREAU COST: \$3,183,768.29






Approach – Building to "Full Cost"

- Begins with a Validated Inventory
- Utilizes Historical Financial Information to develop Multipliers
- Provides a Reasonable,
 Consistent, and Auditable
 Process







Performance Metrics

- Internal
 - "Full Cost" for Asset Stewardship
 - Maintenance standards for all assets
 - Planned versus actual maintenance funding
- External
 - Cost per Unit of Measure to maintain asset
 - Actual funding received per Unit of Measure





Challenges and Lessons Learned

- Challenges
 - Identifying and defining potential Asset Types
 - Staying "out of the weeds"
 - Separating Operations from Maintenance
- Lessons Learned
 - Avoid the "Arms Race" for Maintenance Funding
 - Things are not as unique as they seem (less variation than expected)
 - Part of the value is in the discussion





Summary

- Unit Cost Factors provide a sound methodology for developing annual maintenance funding requirements
- Allows for consistent and equitable development of funding needs across multiple asset types and locations
- Provides "Service Level Standards" by defining appropriate levels of maintenance for each asset type
- Methodology is consistent with current budgeting practices used by Department of Defense and NASA



Reasonable, Consistent, and Auditable



Annual Maintenance Cost Factors

"The Devil Really is in the Details"

2004 Facilities and Asset Management Conference "Stewardship of Federal Assets – United Commitment to Excellence" Orlando Florida May 4-6, 2004



Casey Matthews, P.E.
Utah State Engineer
Bureau of Land Management